

HC-DQ5501N2P-A-LED



Product Features:

- ≥ 5MP high quality image
- ≥ TVI/AHD/CVI/CVBS
- ≥ Supports white light illumination, 24/7 color images
- ≥ 3D noise reduction technology delivers clean and sharp images
- ≥ Supports 180° horizontal flip, 180° vertical flip
- ≥ OSD configuration menu, easy to operate
- ≥ IP67 waterproof and dustproof design, high reliability
- ≥ OSD configuration menu in 11 languages
- ≥ Built-in microphone for high quality audio transmission via coaxial cables



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Sensor	1/3", 5.0 megapixel, CMOS
Min. Illumination	0.01 lux (F1.6, AGC ON) 0 lux (white light on)
Lens	2.8mm
Lens mount	M12
Angle of view(H)	100.9°
Illuminator	One white-light illuminator
Illumination distance	20m
Lifetime	≥60,000 hours
Exposure mode	Four modes: Global (default), BLC, HLC, DWDR
Day/Night	24/7 color images
Digital noise reduction	2D/3D
WDR	DWDR
White balance	Two modes: Auto (default), Manual

VIDEO

Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps: 2592(H)×1944(V); 4MP: 2560(H)×1440(V); 1080P: 1920(H)×1080(V)
Frame Rate	TVI: 5MP@20fps (default), 5MP@12.5fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps AHD: 5MP@20fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps CVI: 5MP@25fps, 4MP@25fps, 4MP@30fps, 1080P@25fps, 1080P@30fps
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s



AUDIO

Microphone

Built-in Mic

Camera audio

TVI: 5MP@20fps, 5MP@12.5fps, 4MP@25fps, 4MP@30fps,
1080P@25fps, 1080P@30fps

CVI: 5MP@25fps, 4MP@25fps, 4MP@30fps

INTERFACE

Power

5.5mm power interface

Video output

BNC, supports TVI/AHD/CVI/CVBS

GENERAL

Power Supply

DC 12V ($\pm 25\%$), with reverse polarity protection, Max 2.3W

Mount

Surface mount (default), optional backbox, wall mount
bracket, pole mount bracket

Operating Temperature

-30°C to 60°C (-22°F to 140°F),

Humidity: $\leq 95\%$ (RH, non-condensing)

Dimensions

$\Phi 118\text{mm} \times 96\text{mm}$ (diameter x height)

Material

Graphene + Plastic

Weight

209g (0.46lb)

Surge protection

4kV

Ingress protection

IP67



An ISO 9001:2008 Certified Company