

HC-DS2401N2PA-DL



Product Features

- ≥ 1080P real-time image, high resolution, true color
- ≥ AHD / TVI / CVI standard and lossless video output
- ≥ CMOS progressive scan, perfectly capturing the moving object
- ≥ Support OSD menu
- ≥ High speed, long distance and real time transmission
- ≥ 20m IR view distance; up to 10m white light view distance
- ≥ Support COC
- ≥ Support coaxial audio transmission
- ≥ Support 960H CVBS output



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1 / 3 "CMOS
Resolution	2MP
Image Size	1920 × 1080
Video Output	AHD / TVI /CVI/CVBS
Audio	1CH built-in MIC
Image System	PAL / NTSC
Electronic Shutter	Auto
View Distance	IR range: 20 m; White light range: up to 10m
Frame Rate	TVI: 2MP@25/30fps AHD: 2MP@25/30fps CVI: 2MP@25/30fps CVBS: PAL/NSTC
Min. Illumination	0.005lux @F1.2, AGC ON; 0 lux (LED ON)
Lens	2.8 mm
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)

FUNCTIONS

Function Control	OSD (COC Control)
Digital WDR	Yes
Digital NR	Yes, 2D DNR (3D, only used with DVRs)
AGC	Yes
Auto White Balance	Yes
BLC	Yes
Contrast	Yes



An ISO 9001:2008 Certified Company

Saturation/Color Gain	Yes
Sharpness	Yes
Coaxial audio	Yes
Image Setting	Yes
Defect Correction	Auto
Language	English
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~90°; Rotation: 0°~360°

GENERAL

Power Supply	DC12V (± 10%)
Power Consumption	LED OFF: < 1W; LED ON: < 3W
Working Environment	-10°C~40°C, 10%~90% (relative humidity)
Dimensions (mm)	∅ 77.5 × 67.6
Weight (Net)	Approx. 0.09KG



An ISO 9001:2008 Certified Company