

## HC-DS5501N2PA-DL



### Product Features

- ≥ 5MP real-time image, high resolution, true color
- ≥ AHD / TVI / CVI lossless HD video output
- ≥ Support 960H CVBS output
- ≥ Up to 1000 TVL resolution
- ≥ CMOS progressive scan, perfectly capturing the moving object Support OSD menu
- ≥ High speed, long distance and real time transmission
- ≥ 24/7 full color imaging
- ≥ LED can be turned on or off automatically
- ≥ Support noise reduction function
- ≥ 20m LED distance
- ≥ IP67
- ≥ Support coaxial audio transmission
- ≥ Support COC



An ISO 9001:2008 Certified Company

## Specifications :

### CAMERA

Image Sensor	1/ 2.7" CMOS
Resolution	5MP
Image Size	2560 x 1936
Video Output	AHD/TVI/CVI/CVBS
Max. IR LEDs Length	30m, 2PCS 3600K soft Warm light
Audio	1CH built-in MIC
Image System	PAL/NTSC
Electronic Shutter	Auto
IR Distance	20m
Frame Rate	30fps (60Hz); 25fps (50Hz)
Min. illumination	0 lux (LED ON)
Lens	2.8mm, horizontal field of view: 107°
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP67

### FUNCTIONS

Function Control	OSD (COC Control)
Smart LED	Manual or Auto mode
ICR	No
Digital WDR	Yes
Digital DNR	Yes, 2D DNR
AGC	Yes
Auto White Balance	Yes
Defog	No
BLC	Yes
Front Light Compensation	No
HLC	Yes
Sharpness	Yes
Contrast	Yes



An ISO 9001:2008 Certified Company

Image Setting

Yes

Defect Correction

Auto

Language

English

Angle Adjustment

Pan: 0°~360° ; Tilt: 0°~75°; Rotation: 0°~360°

**OTHERS**

Power Supply

DC 12V (± 15%)

Power Consumption

LED Off : < 1W ; LED On : < 4W

Working Environment

-30°C ~ 50° C, 10% ~ 90% (relative humidity)

Dimensions (mm)

Φ 94.6 x 82.8

Weight (net)

Approx. 0.39KG



An ISO 9001:2008 Certified Company