

## HC-IPC-D4212W-VF



### Product Features

- ≥ High quality image with 2MP, 1/2.8" CMOS sensor
- ≥ 2MP (1920x1080)@30/25fps; 720P (1280x720)@30/25fps
- ≥ Smart H.265, H.265, H.264
- ≥ Smart IR, up to 30m (98ft) IR distance
- ≥ Day/night functionality
- ≥ 2D/3D DNR (Digital Noise Reduction)
- ≥ Support PoE power supply
- ≥ 3-Axis
- ≥ IP67 Ingress Protection



An ISO 9001:2008 Certified Company

## Specifications :

### CAMERA

Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS
Lens	3.6mm@F2.0
IRIS	Fixed IRIS
Shutter Speed	Auto/Manual, 1 ~ 1/100000s
Day/Night	IR-cut filter with auto switch (ICR)
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON); 0Lux with IR on
IR	Up to 30m (98ft) IR rang
S/N	> 52dB
WDR	DWDR
Noise Reduction	2D/3D DNR
Defog	Digital Defog

### VIDEO

Video Compression	Smart H.265, H.265, H.264
H.264 code profile	Baseline profile, Main profile, High profile
Frame Rate	Profile1: 1080P (1920x1080), Max 30fps; 720P (1280x720), Max 30fps Profile2: D1 (720x576), Max 30fps; 640x360, Max 30fps; 2CIF (704x288), Max 30fps; CIF (352x288), Max 30fps;
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
HLC	Supported
BLC	Supported
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
ROI	Supported
Privacy Mask	Up to 4 areas

### SMART

Basic Detection	Motion detection
-----------------	------------------



## NETWORK

Protocols	IPv4, IPv6, FTP, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, SMTP, NTP, UPnP, HTTP, HTTPS
Compatible Integration	ONVIF (Profile S), API

## INTERFACE

Network	10/100M Base-TX Ethernet
---------	--------------------------

## GENERAL

Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 5.0 W
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F) Humidity ≤ 95% RH (non-condensing)
Surge Protection	4KV
Ingress Protection	IP67



An ISO 9001:2008 Certified Company