

HC-IPC-DQA4113-0280-DL



Product Features :

- ≥ Day/night functionality
- ≥ Max. resolution: 2304 x 1296
- ≥ ICR auto switch, true day / night,
- ≥ 30m Smart Dual Light Colorized Night View
- ≥ 3D DNR, Digital WDR, HLC, BLC, Defog
- ≥ PoE Power Supply
- ≥ Built-in mic
- ≥ Support mobile surveillance by smart phones with iOS and Android OS
- ≥ IP67 Ingress Protection



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/2.7" CMOS
Effective Pixels	2304 x 1296
Electronic Shutter Speed	Auto/Manual, 1/6~1/10,000 s
Min.Illumination	Colour: 0.012 Lux (F1.6, AGC ON) 0 Lux with IR
Iris Type	Fixed Iris

LENS

Lens	2.8mm @F1.6
Angle of View (H)	101.3°
Lens Mount	M12
Wide Dynamic Range	Digital WDR
Digital NR	2D/3D DNR
Angle Adjustment	Pan: 0°~360°, Tilt:0°~75°, Rotation: 0°~360°

IMAGE

Video Compression	Smart H.265, H.264, MJPEG
H.265 Compression Standard	Main Profile @Level4.1 High Tier
Resolution	3MP (2307x1296), 1080P (1920x1080), 720P(1280 x 720), D1(480 x 240), CIF
Main Stream	60Hz: 3MP/1080P/720P(1~30fps) 50Hz: 3MP/1080P/720P(1~25fps)
Bit Rate Type	VBR/CBR
Image Settings	Saturation, Brightness, Chroma, Contrast Wide Dynamics, Sharpen, NR, etc. adjustable through Client Software or Web browser



An ISO 9001:2008 Certified Company

FUNCTIONS

Remote Monitoring

Online Connection

Network Protocol

Smart Alarm

IR Distance

PoE

Audio

Web Browsing, CMS Remote Control

Support Simultaneous monitoring for upto 4 users

Support Multi-Stream Real Time Transmission

UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS,

SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS Storage

Motion detection

30m Smart Dual Light Colorized Night view

Supported

Built-in Mic

INTERFACE

Network

1 RJ45 10/100 Base-TX Ethernet

ELECTRICAL

Power Supply

DC 12V, PoE

Power Consumption

< 5W

ENVIRONMENTAL

Operating Conditions

-20°C ~ 55°C (-4°F~131°F) Humidity

Ingress Protection

IP67



An ISO 9001:2008 Certified Company