

HC-IPC-SDQA20420-4212-WLS



Product Features

- Fixed camera and PTZ camera integration, dual channels with one IP, look at overall situation and consider details at the same time
- High quality image with 2MP, 1/2.8" CMOS sensor
- 1920x1080@25fps in the main stream
- Smart H.265, H.265, H.264, MJPEG
- 4X optical zoom of PTZ channel allows for closer viewing of subjects
- Lighthunter technology ensures ultra-high image quality in low illumination environment
- Up to 120 dB Optical WDR (Wide Dynamic Range)
- Built-in 2xmic & high-power speaker, support two-way audio, has better sound performance
- Support ceiling mount and wall mount
- IR & warm light illumination to deal with different scenes and achieve full-color illumination
- DC12V or PoE+(IEEE 802.3at) power supply



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Sensor
 Lens type

 Optical Zoom
 Iris
 Field of View (H)
 Shutter Speed
 Minimum Illumination

 Day/Night
 IR Range
 Warm Light Range
 Wavelength
 Light On/Off Control
 WDR
 S/N
 White Balance
 Noise Reduction
 Defog

PANORAMA

1/2.8", 2MP, CMOS
 2.8~12mm@F1.6

 Fixed aperture
 102.4°
 Auto/Manual, 1 ~ 1/100000s
 Color:0.002 lux (F1.6, AGC ON)
 0 lux with IR
 IR-cut filter with auto switch (ICR)
 Up to 10m (32.8 ft)

 850nm (IR)
 Auto/Manual
 120dB
 >52dB
 Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
 2D/3D DNR
 Digital defog

DETAIL

2.8~12mm@F1.6, AF automatic
 focusing and motorized zoom lens
 4X

 106.6° ~ 30.6°
 DWDR
 Color:0.002 lux (F1.6, AGC ON)
 0 lux with IR/Warm light

 Up to 50m (164.0 ft)
 Up to 10m (32.8 ft)

VIDEO

Video Compression
 Frame Rate

 Video Bit Rate
 Video stream
 ROI
 OSD

Smart H.265, H.265, H.264, MJPEG
 Main Stream: 1080P (1920x1080), Max 25fps
 Sub Stream: 720P (1280x720), Max 25fps
 128 Kbps~16 Mbps
 Dual streams
 Up to 8 areas
 Up to 4 OSDs



An ISO 9001:2008 Certified Company

Privacy Mask	24 areas, up to 4 areas per scene
Smart IR	Supported
HLC	Supported
BLC	Supported

SMART

Intelligent Analysis	Basic Detection, Motion detection, Audio detection
General Function	Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication

AUDIO

Audio Compression	G.711U, G.711A
Audio Bitrate	64 Kbps
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8 kHz

STORAGE

Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR

NETWORK

Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G), API, SDK



An ISO 9001:2008 Certified Company

PAN & TILT

Pan Range		0° ~ 345°
Pan Speed		1°/s ~ 40°/s Preset speed: 40°/s
Tilt Range	18° ± 5°	-10° ~ 100°
Tilt Speed		1°/s ~ 50°/s Preset speed: 50°/s
Number of Presets	256	
Preset Patrol	16 patrol routes, up to 64 presets for each route	
Patrol Stay Time	1000s~1800s	
Home Position	Support	

INTERFACE

Built-in Mic	Supported (Micx2)	
Built-in Speaker	Supported	
Network	1 RJ45 10M/100M Base-TX Ethernet	

GENERAL

Power	DC12V, PoE+(IEEE 802.3at) Power consumption: Max 24W	
Dimensions (Ø x H)	Wall Mount: Φ134 x 192 x 302mm (Φ5.3" x 7.6" x 11.9") Ceiling Mount: Φ134 x 154 x 363mm (Φ5.3" x 6.1" x 14.3")	
Weight	1.03kg (2.27lb)	
Working Environment	-20 ~ 60 (-4°F ~ 140°F), Humidity: ≤95% RH (non-condensing)	
Storage Environment	-30 ~ 70 (-22°F ~ 158°F), Humidity: ≤95% RH (non-condensing)	
Surge protection	6KV	
Reset button	Supported	

