

HC-IPC-T4744-0600-32G



2MP ANPR NETWORK CAMERA

Product Features

- ≥ HD LPR surveillance camera
- ≥ Auto day/night functionality
- ≥ 2D/3D DNR (Digital Noise Reduction)
- ≥ Up to 120 dB WDR (Wide Dynamic Range)
- ≥ Smart H.265 / H.265+ / H.265 / H.264+ / H.264 / MJPEG
- ≥ 2D/3D DNR (Digital Noise Reduction)
- ≥ Embedded smart algorithm
- ≥ Triple streams,
- ≥ ROI (Region of Interest), ONVIF Conformance
- ≥ Optional network interfaces with Ethernet RJ45 and optical SFP
- ≥ AC 24V /DC 12 V/PoE with uninterruptible power supply
- ≥ 6 KV surge protection designed for network interface



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Sensor	1/2.8" progressive scan, CMOS
Shutter	Auto/Manual, 1/6~1/100000 s
Min. Illumination	Colour: 0.001 Lux (F1.2, AGC ON) B/W:0.001 Lux (F1.2, AGC ON)
Lens	5~50mm @ F1.6, horizontal field of view: 50° ~ 7.1° / 7~22mm@F1.6, motorized (H: 44°~17.6°) (Optional)
Iris	DC-iris
Day& Night	Automatically removable IR-Cut filter(ICR)
Digital Noise Reduction	2D/3D DNR
S/N	>52dB
Defog	Optical Defog & Digital Defog
WDR	120 dB

VIDEO

Video Compression	Smart H.265 / H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 code Profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream:2MP (1920×1080): Max. 60 fps; Sub Stream: 720P: Max. 30 fps; Third Stream: D1/CIF/480x240Max. 30 fps
HLC	Supported
BLC	Supported
ABF	Supported
OSD	Up to 4 OSD
ROI	Up to 4 areas
Privacy mask	Up to 4 areas

SMART

Image Settings:	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
Intelligent Identification	Scene change detection, video tampering detection, license plate recognition, motion detection
General Function	Watermark, IP address filtering, video mask, heartbeat, password protection, non-photosensitive switch, image distortion correction
Smart IR	100mtr



An ISO 9001:2008 Certified Company

LPR

Snapshot	Overview and cutout of plate for picture
White List	10000
Capture Speed Range	0 ~ 70km/h

AUDIO

Audio Compression	G.711
Two-way audio	Supported
Suppression	Supported

STORAGE

Edge Storage	Micro SD, up to 128 GB / 256 GB (Optional)
Network storage	NAS (Network Attached Storage) Local PC for instant recording

NETWORK

Protocols	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF (Profile S, Profile G) API
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission

INTERFACE

Audio I/O	3.5 mm audio interface Input: impedance 35 k Ω ; amplitude 2 V [p-p] Output: impedance 600 Ω ; amplitude 2 V [p-p]
Alarm I/O	1 / 1
Network	1 RJ45 10/100M

GENERAL

Power	12 V DC \pm 25% / PoE
Dimensions (L x W x H)	Power consumption: 11 W 279.5 x 100.3 x 88.9
Weight	1.04kg (2.2 lb)
Working Environment	-30 $^{\circ}$ C ~ 60 $^{\circ}$ C (-22 $^{\circ}$ F~140 $^{\circ}$ F), Humidity: less than 95 % (non-condensing)

