

**HC-IPC-TQA4114-0360-DLS**



## Product Features

- ≥ Day/night functionality
- ≥ Max. resolution: 2560 x 1440
- ≥ ICR auto switch, true day / night,
- ≥ 30m Smart Dual Light Colorized Night View
- ≥ 3D DNR, Digital WDR, HLC, BLC, Defog
- ≥ PoE Power Supply
- ≥ Built-in Mic and Speaker
- ≥ Support mobile surveillance by smart phones with iOS and Android OS
- ≥ IP67 Ingress Protection



An ISO 9001:2008 Certified Company

## Specifications :

### CAMERA

Image Sensor	1/2.9" CMOS
Effective Pixels	2560 x 1440
Electronic Shutter Speed	Auto/Manual, 1/6~1/10,000 s
Min.Illumination	Colour: 0.012 Lux (F1.6, AGC ON) 0 Lux with IR
Iris Type	Fixed Iris

### LENS

Lens	3.6mm @F1.6, horizontal field of view: 70°
Lens Mount	M12
Wide Dynamic Range	Digital WDR
Digital NR	2D/3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt:0°~75°; Rotation: 0°~360°

### IMAGE

Video Compression	Smart H.265, H.264, MJPEG
H.265 Compression Standard	Main Profile @Level4.1 High Tier
Resolution	4MP (2560x1440), 3MP (2307 x 1296), 1080P (1920 x 1080), 720P (1280 x 720), D1(480 x 240), CIF
Main Stream	60Hz: 3MP/1080P/720P(1~30fps) 50Hz: 3MP/1080P/720P(1~25fps)
Bit Rate Type	VBR/CBR
Image Settings	Saturation, Brightness, Chroma, Contrast Wide Dynamics, Sharpen, NR, etc. adjustable through Client Software or Web browser



An ISO 9001:2008 Certified Company

## **FUNCTIONS**

Remote Monitoring

Online Connection

Network Protocol

Audio

Smart Alarm

IR Distance

PoE

Web Browsing, CMS Remote Control

Support Simultaneous monitoring for upto 4 users

Support Multi-Stream Real Time Transmission

UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS,

SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS Storage

Built-in Mic and Speaker

Motion detection

30m Smart Dual Light Colorized Night view

Supported

## **INTERFACE**

Network

1 RJ45 10/100 Base-TX Ethernet

## **ELECTRICAL**

Power Supply

DC 12V, PoE

Power Consumption

< 5W

## **ENVIRONMENTAL**

Operating Conditions

-20°C ~ 55°C (-4°F~131°F) Humidity

Ingress Protection

IP67



An ISO 9001:2008 Certified Company