

HC-IPC-TS4401MVFN5-DL



Product Features

- ≥ H.265+/H.265 /H.264+/H.264/MJPEG coding
- ≥ Max. resolution: (2560 × 1440)
- ≥ ICR auto switch, true day / night vision
- ≥ 30m white light view distance; 50m IR view distance
- ≥ 3D DNR,DWDR, HLC, BLC, etc
- ≥ Support Dual streams
- ≥ DC12V/PoE power supply
- ≥ Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- ≥ IP67 Ingress Protection



An ISO 9001:2008 Certified Company

SPECIFICATIONS:

CAMERA

Sensor	1/3", Progressive scan, 4.0megapixel, CMOS
Lens	2.8~12mm @F1.4 Motorized Zoom Lens
Angle of view(H)	92.5° ~34°
Shutter Speed	1/2 s ~ 1/100000 s
Day/Night	IR-cut filter with auto switch (ICR)
Min.Illumination	0.03 lux @F1.4, AGC ON; 0 lux with IR
WDR	Digital WDR
Digital NR	Supported
HLC	Supported
BLC	Supported
Angle Adjustment	Pan: 0°~360°; Tilt:0°~90°;Rotation: 0°~360°

VIDEO

Video Compression	H.265+(Smart H.265), H.265, H.264, MJPEG
H.265 Compression Standard	Main Profile@Leve4.1 High Tier
Resolution	4MP (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF
Main Stream	4MP/3MP/1080P/720P(1~30fps)
Sub Stream	D1/VGA/CIF (1~30fps)
Video Bit Rate	64Kbps~3Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, NR, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately



INTERFACE

Network	1 RJ45 10M/100M Base-TX Ethernet
Audio	1CH Built-in -Mic

FUNCTIONS

Remote Monitoring	Web browser /NVR/NVMS2.X/Mobile APP
Online Connection	Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Network Protocol	TCP/IP, UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, SNMP, UPnP, HTTP, HTTPs, QoS
Interface Protocol	ONVIF (Profile S, G, T)
Storage	Network remote storage
Smart Alarm	Motion detection
General Function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock
PoE	Supported
Supplement Light Range	IR range: 50 m; white light range: 30 m

GENERAL

Power	DC12V/PoE Power consumption: < 8W
Working Environment	-30°C ~ 60°C ,(-22°F~140°F) less than 95%(non-condensing)
Ingress Protection	IP67
Dimensions (mm)	217.7 × 80.5 × 80.3

