

HC-T2401N3P-A



Product Features

- ≥ 1080P real-time image, high resolution, true color
- ≥ AHD / TVI / CVI lossless HD video output
- ≥ Support 960H CVBS output
- Support 1CH Built-In MIC
- Support OSD menu
- High speed, long distance and real time transmission
- Support noise reduction function
- Support noise reduction function
- Support coaxial audio transmission
- ≥ IP67



An ISO 9001:2008 Certified Company





Specifications:

CAMERA

Sensor 1/2.8", progressive scan, 2.4 megapixel, CMOS

Lens 2.8mm

Shutter Speed Auto

Min. Illumination Color: 0 lux (IR ON)

AWB (Auto white balance) Auto/Natural/Street Lamp/Outdoor/Manual

Digital zoom 16x

Noise Reduction 2D DNR

HLC Supported

BLC Supported

Lens Mount M12

OSD Supported

Audio Compression G.711

Image Settings Rotate Mode, Saturation, Brightness, Contrast,

Sharpness adjustable by client software or web browser





INTERFACE

Audio 1CH Audio Built-In MIC

Video Output AHD / TVI /CVI/CVBS

GENERAL

Power 12 V DC±15%

Power consumption: Max 4 W

Working Environment -30°C to 50°C

Humidity 10% ~ 90% RH(non-condensing)

Ingress Protection IP67

Weight 0.37kg

Dimensions $165.7 \times 69 \times 69$

