

HC-TQ2401N2P-A-LED



Product Features:

- ≥ 2MP high quality image
- ≥ TVI/AHD/CVI/CVBS
- ≥ Supports white light illumination, 24/7 color images
- ≥ Supports 180° horizontal flip, 180° vertical flip
- ≥ OSD configuration menu, easy to operate
- ≥ IP67 waterproof and dustproof design, high reliability
- ≥ OSD configuration menu in 11 languages
- ≥ Built-in-Mic



Specifications :

CAMERA

Sensor	1/3", 2.0 megapixel, CMOS
Min. Illumination	0.01 lux (F1.6, AGC ON) 0 lux (white light on)
Lens	4.0mm
Lens mount	M12
Angle of view(H)	82.5°
Illuminator	One white-light illuminator
Illumination distance	20m
Lifetime	≥60,000 hours
Exposure mode	4 modes: Global (default), BLC, HLC, DWDR
Day/Night	24/7 color images
Digital noise reduction	2D/3D
WDR	DWDR
White balance	Two modes: Auto (default), Manual

VIDEO

Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame Rate	TVI/AHD/CVI: 1080P@30fps, 1080P@25fps; 720P@30fps, 720P@25fps CVBS: PAL, NTSC
Shutter time	PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s

INTERFACE

Power	5.5mm power interface
Video output	BNC, supports TVI/AHD/CVI/CVBS



GENERAL

Power Supply	DC 12V ($\pm 25\%$), with reverse polarity protection, Max 2.4W
Mount	3D bracket supplied, surface mount (default), optional backbox, pole mount bracket
Operating Temperature	-30°C to 60°C (-22°F to 140°F), Humidity: $\leq 95\%$ (RH, non-condensing)
Dimensions	142mm x 63mm x 65mm (L x W x H)
Material	Plastic
Weight	145g (0.32lb)
Surge protection	4kV
Ingress protection	IP67



An ISO 9001:2008 Certified Company