

HD-NVR-4116TL- A



Product Features

- ≥ 16 CH Support 8MP/ 6MP/ 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- ≥ Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- ≥ Multi-mode recording: manual / timer / motion / sensor
- ≥ Playback :16 CH simultaneous playback
- ≥ Search : time slice, time, event (manual, sensor, motion), tag search
- ≥ Express and flexible backup via USB, network and so on
- ≥ Pentaplex : preview, record, playback, backup and remote access



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

OS Embedded Linux

VIDEO

Incoming Bandwidth 112Mbps
Outgoing Bandwidth 112Mbps
Video Compression Smart H.265, H.265, H.264
Input Resolution 8MP, 6MP, 5MP, 4MP, 3MP,
1080P, 960P, 720P@25/30fps
Network Access 16 CH IPC Input
Output HDMI×1: 3840×2160/1920×1080/
1280×1024/1024×768
VGA×1: 1920×1080/1280×1024/1024×768

AUDIO

Input RCA × 1
Local Output RCA × 1

RECORD

Resolution 8MP, 6MP, 5MP, 4MP, 3MP,
1080P, 960P, 720P@25/30fps
Record Stream Dual stream recording
Mode Manual, Timer, Motion, Sensor

PLAYBACK

Simultaneous Playback Max 16 CH
Search Time slice/time/event/tag search
Smart Search Highlight colors to display the camera record in a
certain period of time, different colors refer to different
record events
Function Play, Pause, FF, FB, Digital zoom, etc

ALARM

Mode Manual, sensor, motion, exception
Trigger Record, Snap, Preset, E-mail, etc



An ISO 9001:2008 Certified Company

NETWORK

Interface	RJ45 1000 Mbps × 1
Protocol	IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP, HTTPS, FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF

MOBILE DEVICE

OS	iOS,Android
----	-------------

STORAGE

HDD	SATA×1,Up to 8TB per HDD
-----	--------------------------

BACKUP

Local Backup	U disk, USB Mobile HDD
Network Backup	Supported

PORT

USB	USB 2.0 ×2 (rear panel)
-----	--------------------------

ELECTRICAL CHARACTERISTICS

Power Supply	DC 12V/1.5A
Consumption	≤ 10W (without HDD)
Working Environment	-10 ~ 50 °C, 10% ~ 90% humidity
Dimension (mm)	300×248×52(W×D×H)



An ISO 9001:2008 Certified Company