

## HD-NVR-4324H4-4K



### Product Features :

- Support 40CH /12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF IP input
- H.265S/H.265+/H.265/H.264 coding
- Intuitive and user-friendly Graphic User Interface ( GUI ), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor/ POS / AI recording
- Playback : 16 CH simultaneous playback
- Search: time slice, time, event, tag, smart search
- Support face detection and comparison
- Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
- Support license plate recognition
- Support POS information overlay on live view and playback
- Support RAID 0, 1, 5, 6, 10
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS



## Specifications :

### SYSTEM

OS Embedded Linux

### VIDEO

IP Video Input 40 CH IPC input  
Incoming Bandwidth 192Mbps  
Outgoing Bandwidth 192Mbps  
Resolution 12MP/8MP/6MP/5MP/4MP/3MP/1080P/  
1280x1024/960P/720P/960H/D1/CIF

Output HDMI : 3840× 2160/1920 × 1080/1280× 1024 × 768  
HDMI2 : 1920 × 1080 / 1280 × 1024 / 1024 × 768  
VGA ×1 / 1280 × 1024 × 768  
VGA and HDMI1 output the same video source

Compression H.265S / H.265+ /H.265 /H.264

### AUDIO

Network Input 40 CH  
Local Input RCA×1 (for two-way talk  
Local Output RCA×1  
HDMI Audio Output Support  
Compression G.711 (U/A)

### RECORD

Resolution 12MP/8MP/6MP/5MP/4MP/3MP/1080P/  
1280x1024/960P/720P/960H/D1/CIF

Frame Rate NTSC: 30fps; PAL: 25fps



An ISO 9001:2008 Certified Company

### PLAYBACK

Simultaneous Playback  
Search  
Smart Search

16 CH  
Time slice / time / event / tag /smart search  
Highlighted color to display the camera record in a certain period of time, different colors refers to different record events

Function

Play, pause, FF, FB, digital zoom, etc

### DECODING CAPABILITY

Live View/Playback

1CH 12MP/4CH 1080P

### MULTI-SCREEN DISPLAY MODE

Mode

Dual output mode (default mode): supports HDMI2 output, but doesn't support AI by device AI mode: HDMI2 output and 12MP video input (live view/playback) are unavailable, but 8MP video input supports

### ALARM

Mode  
Input  
Output  
Triggering

Manual, sensor, motion, exception, smart events, etc.  
16 CH local alarm input  
8CH  
Record, snapshot, preset, e-mail, etc.

### FACE RECOGNITION

Face Detection Performance (AI by IPC) 40CH  
Face Detection Performance (AI by Device) 2CH  
Face Match Performance 6CH  
Comparison Capability 18 pictures/second  
Face Picture Database 32 libraries 10000 face pictures  
Face Picture search Search by picture is supported  
Database Management Add, modify, delete and search face pictures  
Face Picture Adding Add face pictures through APP, WEB and external import  
Face Picture Comparison Support allow list, block list and stranger match alarm  
Track Track display on a map  
Statistical Graph of Information Bar graph

40CH  
2CH  
6CH  
18 pictures/second  
32 libraries 10000 face pictures  
Search by picture is supported  
Add, modify, delete and search face pictures  
Add face pictures through APP, WEB and external import  
Support allow list, block list and stranger match alarm  
Track display on a map  
Bar graph



Statistical Mode of Information

Statistics by day, week, month, quarter as well as customized time period

**VIDEO STRUCTURE ANALYSIS**

Human/Vehicle Classification

Yes

**FUNCTION**

Fisheye Access

Supports fisheye dewarping via Web Client and mobile APP Plate

Recognition

Yes

**NETWORK**

Interface

RJ45 1000Mbps ×2

Protocol

TCP / IP, IPv4, IPv6, RTP, RTSP, RTCP, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPS, 802.1x, SNMP, ONVIF, etc.

Client Connection

Max. 20 users access

**MOBILE DEVICE**

OS

iOS, Andriod

**STORAGE**

HDD Interface

SATA×4 max 16TB per HDD

E-SATA

Interface 2

**BACKUP**

Local Backup

U disk, USB mobile HDD

Network Backup

Yes

**EXTERNAL INTERFACE**

RS 485

Yes (full-duplex), connect to PTZ or keyboard

USB

USB 3.0 1 ; × USB 2.0 × 2

Remote Controller

Optional

**ELECTRICAL**

Power Supply

ATX-250W

Consumption

≤ 20W ( without HDD )

**ENVIRONMENTAL**

Dimensions (mm)

440 × 390 × 70( W × D × H )

Working Environment

-10 ~ 50 °C, 10% ~ 90% humidity

