

HD-NVR-4328H8-4K



Product Features

- ≥ 32 CH Support 12MP/ 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- ≥ Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- ≥ Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse,4K Output True High Resolution Display
- ≥ Multi-mode recording: manual / timer / motion / sensor
- ≥ Playback :16 CH simultaneous playback
- ≥ Search : time slice, time, event (manual, sensor, motion), tag search
- ≥ Express and flexible backup via USB, network and so on
- ≥ Pentaplex : preview, record, playback, backup and remote access
- ≥ DHCP, DDNS, PPPoE network protocol and CMS supported
- ≥ Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- ≥ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device,Multi-user online simultaneously
- ≥ Authorization management, log view and device status view,4K output, true high resolution display
- ≥ Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- ≥ Support NAT function and QRCode scanning by mobile phone and PAD
- ≥ Powerful smart phone & Pad surveillance with iOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

Compression	H.265 Standard
OS	Embedded Linux

VIDEO

Network Input	32 CH IPC Input
Video Compression	Smart H.265, H.265, H.264
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
Input Resolution	12MP, 8MP, 5MP, 4MP, 3MP, 1080P, 960P, 720@25/30fps
Output	HDMI×2:one 4K×2K/1920×1080/1280×1024 1920×1080/1280×1024 VGA×1:1920×1080/1280×1024

AUDIO

Input	32 CH IPC audio input
2-way Audio	RCA ×1
Local Output	RCA ×1

RECORD

Resolution	12MP, 8MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P
Record Stream Mode	Dual Stream Recording Manual, Timer, Motion, Sensor

PLAYBACK

Simultaneous Playback	Max 16 CH
Search	Time Slice/Time/Event/Tag Search
Smart Search	Highlighted Color to Display the Camera recording a Certain Period of Time, Different Color refer to Different Record Events
Function	Play, Pause, FF, FB, Digital Zoom, etc

ALARM

Mode	Manual, Sensor, Motion, Exception
------	-----------------------------------



An ISO 9001:2008 Certified Company

Input 8 CH Local alarm Input,Support IPC Alarm Input
Output 4 CH
Triggering Record, Snap, Preset, Email, etc

INTELLIGENT ANALYTICS

Face Support Face Detection, Face Recognition,Face
Comparison Support Search Image by Image

NETWORK

Interface RJ45 10/100/1000 Mbps × 2
Network Protocol IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP, HTTPS,
FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF
Array Type RAID 0,1,5,6,10
Web Client Maximum 10 user online

MOBILE DEVICE

OS iOS Andriod

STORAGE

HDD SATA×8,e-SATA×2,max 16TB per HDD

BACK UP

Local Backup U Disk, USB Mobile HDD
Network Backup Yes

PORT

USB USB 2.0×2, USB 3.0×1
Remote Controller Yes

ELECTRICAL

Power Supply ATX
Consumption ≤30W(without HDD)

ENVIRONMENTAL

Work Environment -10~50 °C, 10%~ 90% humidity
Dimensions(mm) 445×436×90(W×D×H)



An ISO 9001:2008 Certified Company