

HD-NVR-5116S



Product Features

- ≥ 8-Channel input
- ≥ Third-party IP cameras supported with ONVIF conformance
- ≥ Support 1-CH HDMI, 1-CH VGA, HDMI at up to 4K(3840x2160) resolution
- ≥ Up to 8 Megapixels resolution recording
- ≥ Support H.265/H.264 video formats
- ≥ Accurate retrieval, instant playback
- ≥ 1 SATA HDD up to 8 TB
- ≥ Support for P2P, UPnP, NTP, DHCP, PPPoE
- ≥ Support for mobile client access



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

Compression Smart H.265/H.264

VIDEO

Network Access Bandwidth 80 Mbps Incoming/ 80 Mbps Outgoing
Recording Resolution 8MP/6MP/5MP/4MP/3MP/1080p/960p/
720p/D1/2CIF/CIF
IP Video Input 8-ch
HDMI/VGA Output HDMI:4K (3840x2160) /30Hz, 1920x1080p /60Hz,
1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024
/60Hz, 1280x720 /60Hz, 1024x768 /60Hz
VGA:1920x1080p /60Hz, 1920x1080p /50Hz,
1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720
/60Hz, 1024x768 /60Hz
Protocols HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP,
DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server,
P2P

AUDIO

Audio Output 1-ch, RCA
Two-way Audio Input 1-ch, RCA

PLAYBACK

Simultaneous Playback 8-ch
Live View Display 8MP/6MP/5MP/4MP/3MP/1080p/960p/
720p/D1/2CIF/CIF
Remote Users 128



An ISO 9001:2008 Certified Company

HARD DISK

SATA

1 SATA interfaces

Capacity

up to 8TB for each disk

SMART

VCA Detection

Intrusion detection, Cross line detection, Motion detection,

EXTERNAL INTERFACE

Network Interface

1 RJ-45 10M/100M self-adaptive Ethernet

Interfaces

USB Interface

Rear panel : 2 x USB2.0, Front panel : 1XUSB2.0

Alarm In

4-ch

Alarm Out

1-ch

GENERAL

Power Supply

12V DC

Power Consumption: ≤ 8W (without HDD)

Working Environment

-10°C~+ 55°C (+14°F~+131°F)

Humidity ≤ 10% ~90% RH (non-condensing)



An ISO 9001:2008 Certified Company