

HD-NVR-5216SHP



Product Features

- ≥ Support Smart H.265/H.265/H.264 video formats
- ≥ 16-Channel input
- ≥ Third-party IP cameras supported with ONVIF conformance Profile S, Profile G, Profile T
- ≥ Support 1-Ch HDMI, 1-Ch VGA, HDMI at up to 4K(3840x2160) resolution
- ≥ HDMI and VGA simultaneous output
- ≥ Up to 12 Megapixels resolution recording
- ≥ 2 SATA HDDs, Up to 10TB for each disk
- ≥ Various fisheye dewarping modes for live view and playback for both web interface and GUI
- ≥ ANR technology to enhance the storage reliability when the network is disconnected
- ≥ Support cloud upgrade



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

Compression Smart H.265, H.265, H.264

VIDEO

Network Access Bandwidth 160 Mbps Incoming/ 160 Mbps Outgoing
 Recording Resolution 12MP/8MP/6MP/5MP/4MP/3MP/1080p/
 960p/720p/D1/2CIF/CIF
 IP Video Input 16-ch
 HDMI/VGA Output HDMI:4K (3840x2160) /60Hz, 4K (3840x2160)
 /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz,
 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720
 /60Hz, 1024x768 /60Hz
 VGA: 1920x1080p /60Hz, 1920x1080p /50Hz,
 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768
 /60Hz
 Protocols P2P, UPnP, NTP, DHCP, PPPoE

AUDIO

Audio Output 1-ch, RCA
 Two-way Audio Input 1-ch, RCA

PLAYBACK

Simultaneous Playback 16-ch
 Live View Display 12MP/8MP/6MP/5MP/4MP/3MP/1080p/
 960p/720p/D1/2CIF/CIF
 Corridor Mode Screen 3/4/5/7/9/10/12/16
 Remote Users 128



An ISO 9001:2008 Certified Company

HARD DISK

SATA

2 SATA interfaces

Capacity

Up to 10TB for each disk

SMART

VCA Detection

Intrusion detection, Line

Crossing detection, Motion detection

EXTERNAL INTERFACE

Network Interface

1 RJ45 10M/100M/1000M self-adaptive Ethernet

Interfaces

USB Interface

Front panel: 1 x USB2.0

Rear panel: 1 x USB2.0, 1 x USB3.0

Alarm In

4-ch

Alarm Out

1-ch

GENERAL

Power Supply

12V DC

Power Consumption: ≤ 20W (without HDD)

Working Environment

-10°C~+ 55°C (+14°F~+131°F)

Humidity ≤ 90% RH (non-condensing)



An ISO 9001:2008 Certified Company