

HD-NVR-5232L



Product Features

- ≥ Support H.265(Smart Encode)/H.265/H.264 Video formats
- ≥ 32-channel input
- ≥ Third-party IP cameras supported with ONVIF conformance Profile S, Profile G, Profile C, Profile Q, Profile A, Profile T
- ≥ Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840x2160) resolution
- ≥ Up to 5 Megapixels resolution recording
- ≥ HDMI and VGA simultaneous output
- ≥ 2 SATA HDD up to 6 TB for each HDD
- ≥ ANR technology to enhance the storage reliability when the network is disconnected



An ISO 9001:2008 Certified Company

Specifications :

VIDEO/AUDIO INPUT

IP Video Input	32-Channel
Two-way Audio Input	1-Ch, RCA

NETWORK

Incoming Bandwidth	64Mbps
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP HTTPS, FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF

VIDEO/AUDIO INPUT

HDMI/VGA Output	HDMI: 4K (3840x2160) /30Hz, 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz VGA: 1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
Recording Resolution	5MP/4MP/3MP/1080p/960p/720p/D1/ 2CIF/CIF
Audio Output	1-Ch, RCA
Synchronous Playback	16-Channel



An ISO 9001:2008 Certified Company

DECODING

Compression	Smart H.265, H.265, H.264
Live view/ Playback	5MP/4MP/3MP/1080p/960p/720P/ D1/2CIF/CIF
Capability	1 x 4K@30, 2 x 4MP@30, 4 x 1080p@30, 8 x 720p@30

HARD DISK

SATA	2 SATA interface
Capacity	Up to 6TB for each Disk

EXTERNAL INTERFACE

Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
USB Interface	Rear panel: 2 x USB2.0

GENERAL

Power Supply	12V DC
Power Consumption (without HDD)	≤ 5 W
Working Temperature	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions	260.0mm × 240.2mm ×43.6mm (10.2"× 9.5"×1.7")
Weight (without HDD)	≤ 1 Kg (2.2 lb)



An ISO 9001:2008 Certified Company