

HD-NVR-5232Q



Product Features

- ≥ Support Smart H.265/H.265/H.264 video formats
- ≥ 32-channel input
- ≥ Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
- ≥ HDMI and VGA simultaneous output
- ≥ Up to 8 Megapixels resolution recording
- ≥ Accurate retrieval, instant playback
- ≥ 2 SATA HDDs, up to 10TB for each HDD
- ≥ ANR technology to enhance the storage reliability when the network is disconnected
- ≥ Support cloud upgrade



An ISO 9001:2008 Certified Company

Specifications :

IP VIDEO INPUT

IP Video Input	32-ch
Two-way Audio Input	1-ch, RCA

NETWORK

Incoming bandwidth	160Mbps
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP

VIDEO/AUDIO INPUT

HDMI/VGA Output	HDMI: 4K (3840x2160) @30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60 VGA: 1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Audio Compression	G.711A, G.711U
Synchronous Playback	16-ch
Liveview display	1/4/6/8/9/16/25/36
Corridor Mode Screen	3/4/5/7/9/10/12/16/32



An ISO 9001:2008 Certified Company

SNAPSHOT

FTP/Schedule/Event Snapshot

1-ch snapshot, up to D1 resolution

DECODING

Decoding format

Smart H.265/H.265/H.264

Liveview/Playback

8MP/6MP/5MP/4MP/3MP/1080p/960p/

720p/D1/2CIF/CIF

Capability

2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30,

8 x 1080p@30, 16 x 720p@30,32 x D1

HARD DISK

SATA

2 SATA interface

Capacity

Up to 10TB for each disk

SMART

VCA Detection by Camera

Intrusion Detection, Line Crossing Detection,

Enter Area, Leave Area, Audio Detection

VCA Search

Behavior Search

People counting

People Flow Counting, Crowd Density Monitoring

GENERAL ALARM

General Alarm

Motion, Tampering, Human Body Detection,

Video Loss, Alarm Input, Audio Detection

Alert Alarm

IP Conflict, Network Disconnected, Disk Offline, Disk

Abnormal, Illegal Access, Hard Disk Space Low,

Hard Disk Full, Recording/Snapshot Abnormal



An ISO 9001:2008 Certified Company

EXTERNAL INTERFACE

Network interface

2 RJ-45 10M/100M/1000M

self-adaptive Ethernet Interface

USB interface

Rear panel: 1 x USB2.0, 1 x USB3.0,

Front panel: 1 x USB2.0

GENERAL

Power supply

12V DC

Power Consumption: ≤5 W (without HDD)

Working Environment

-10°C ~ + 55°C (+14°F ~ +131°F),

Humidity ≤ 90% RH (non-condensing)

Dimensions (W×D×H)

380mm × 315mm ×53mm (15.0" × 12.4" ×2.1")

Weight

≤ 2.48 Kg (5.47 lb)



An ISO 9001:2008 Certified Company