

HD-NVR-5232T-A



Product Features

- 32 CH Support 8MP / 6MP/ 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse,4K Output True High Resolution Display
- Multi-mode recording: manual / timer / motion / sensor
- Playback :16 CH simultaneous playback
- Search : time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device,Multi-user online simultaneously
- Authorization management, log view and device status view,4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

OS Embedded Linux

VIDEO

Network Input 32 CH IPC Input
Video Compression Smart H.265, H.265, H.264
Incoming Bandwidth 160 Mbps
Outgoing Bandwidth 160 Mbps
Input Resolution 8MP,6MP,5MP,4MP,3MP,1080P,960P,
720@25/30fps
Output HDMI×1: 3840×2160/1920×1080/1280×1024/ 1024×768
VGA×1:1920×1080/1280×1024/ 1024×768

AUDIO

Input 32 CH IPC audio input
2-way Audio RCA ×1
Local Output RCA ×1

RECORD

Resolution 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P
Record Stream Dual Stream Recording
Mode Manual, Timer, Motion, Sensor

PLAYBACK

Simultaneous Playback Max 16 CH
Search Time Slice/Time/Event/Tag Search
Smart Search Highlighted Color to Display the Camera record in a
Certain Period of Time, Different Color refer to
Different Record Events
Function Play, Pause, FF ,FB, Digital Zoom,etc

ALARM

Mode Manual, Sensor, Motion, Exception
Input 8 CH Local alarm Input, 32 CH IPC Alarm Input
Output 4 CH



An ISO 9001:2008 Certified Company

Triggering

Record, Snap, Preset, Email, etc

SMART

VCA Detection

Intrusion detection, Cross line detection
Audio detection, Defocus detection, Object Left, Missing
Object, Scene change detection, Auto tracking
Behavior search

VCA Search

NETWORK

Interface

RJ45 10/100/1000 Mbps × 1

Network Protocol

IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP,
HTTPS, FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF
Multiple user online

Web Client

MOBILE DEVICE

OS

iOS Andriod

STORAGE

HDD

SATA×2,max 8TB per HDD

RS 485

Yes (full-duplex), connect to PTZ or keyboard

BACK UP

Local Backup

U Disk,USB Mobile HDD

Network Backup

Yes

PORT

USB

USB 3.0×1,USB 2.0×1 (one in the front panel and
other in the Rear panel)

Remote Controller

Yes

ELECTRICAL

Power Supply

DC12V/4A

Consumption

≤10W(without HDD)

ENVIRONMENTAL

Work Environment

-10~50 °C, 10%~ 90% humidity

Dimensions(mm)

380 × 268 × 45 (W × D × H)



An ISO 9001:2008 Certified Company