


HD-NVR-5240T-B



Product Features

- Support 40CH 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/ 960P/720P/960H/DI/CIF IP video input
- H.265S / H.265+ / H.265 / H.264 coding
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Search: time slice, time, event, tag and smart search
- Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
- Support POS information overlay on live view and playback
- Playback: 16CH simultaneous playback
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K ultra high resolution output, true high resolution display
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

OS Embedded Linux

VIDEO

Network Input 40CH IPC input

Network Input Resolution 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/
960H/D1/CIF

Output HDMI × 1: 3840 × 2160 / 1920 × 1080 / 1280 × 1024/ 1024 × 768
VGA: 1920 × 1080 / 1280 × 1024/ 1024 × 768

Screen Display Mode 1/4/6/8/9/13/16/25/32/36

Compression H.265S/H.265+/H.265/H.264

AUDIO

Network input 40 CH IPC audio input

Local Input RCA × 1 (for two-way audio)

Local Input RCA × 1

Compression G.711 (U/A)

RECORD

Resolution 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/
960H/D1/CIF

Frame Rate NTSC: 30fps; PAL: 25fps

PLAYBACK

Simultaneous Playback Max 16CH

Search Time slice/time/event/tag search

Smart Search Highlighted color to display the camera record in a certain period
of time, different colors refers to different record events

Function Play, pause, FF, FB, digital zoom, etc



An ISO 9001:2008 Certified Company

DECODING CAPABILITY

Live View/Playback

Non-AI Mode: 4×4MP@30fps/9×1080P@30fps/16×720P@30fps

AI Mode: 4×3MP@30fps/9×720P@30fps/16×D1@30fps

ALARM

Mode

Manual, sensor, motion, exception, smart events

Input

4CH alarm input; IPC alarm input supported

Output

1CH alarm output; IPC alarm output supported

Triggering

Record, snap, preset, e-mail, etc.

NETWORK

Interface

1 x RJ45 1000Mbps

Protocol

TCP / IP, IPv4, IPv6, UDP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, HTTP, SMTP, HTTPS, 802.1x, RTSP, RTP, RTCP, FTP, WebSocket, SNMP, IGMP, ONVIF

Bandwidth

Incoming: 192Mbps

Outgoing: 192Mbps

Client Connection

Max. 128 users

FACE

Face Detection Performance

(AI by IPC)

40CH

Face Detection Performance

(AI by Device)

2 CH (2MP)

Statistical Graph of Information

Bar graph

Statistical Mode of Information

Statistics by day, week, month, quarter as well as Customized time period



An ISO 9001:2008 Certified Company

PERIMETER PROTECTION

| | |
|--|-----------|
| Human/Vehicle Classification (AI by IPC) | 40 CH |
| Human/Vehicle Classification (AI by Device) | 2CH (2MP) |

VIDEO METADATA

| | |
|---|-----|
| Human/Vehicle Attribute Analysis (AI by IPC) | Yes |
|---|-----|

OTHER FUNCTIONS

| | |
|-------------------------------|--|
| Fisheye | Supports fisheye dewarping via Web Client/mobile APP |
| Plate Recognition (AI by IPC) | Yes |

MOBILE DEVICE

| | |
|----|--------------|
| OS | iOS, Andriod |
|----|--------------|

STORAGE

| | |
|---------------|-------------------------------|
| HDD Interface | SATA3.0 × 2, max 10TB per HDD |
|---------------|-------------------------------|

BACKUP

| | |
|----------------|------------------------|
| Local Backup | U disk, USB mobile HDD |
| Network Backup | Yes |

PORT

| | |
|-------------------|---|
| USB | USB 2.0 × 2; USB 3.0 × 1 |
| RS485 | Yes (full-duplex); connect to PTZ or keyboard |
| Remote Controller | Optional |



An ISO 9001:2008 Certified Company

GENERAL

| | |
|---------------------|--------------------------------|
| Power Supply | DC 12V/3A |
| Consumption | ≤ 10W (without HDD) |
| Dimensions (mm) | 380 × 268 × 45 (W × D × H) |
| Working Environment | -10 ~ 50°C, 10% ~ 90% humidity |



An ISO 9001:2008 Certified Company