

HD-NVR-7240T



Product Features

- Support 40CH 16MP/12MP/9MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF IPC Input
- H.265S/H.265+/H.265/H.264
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-type recording: manual / timed / motion / sensor / POS / AI recording
- Playback: 16 CH simultaneous playback
- Search: time slice, time, event, tag and smart search
- Support face detection and comparison
- Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
- Support license plate recognition
- Support POS information overlay on live view and playback
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Compatible with third-party IPCs, such as ONVIF, etc.
- Remote control via Web Client or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

OS Embedded Linux

VIDEO

Compression H.265S/H.265+/H.265/H.264

IP Video Input 40CH IPC input

Resolution 16MP/12MP/9MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/
960P/ 720P/960H/D1/CIF

Network Bandwidth Incoming: 320Mbps
Outgoing: 320Mbps

Output HDMI1: 3840 × 2160/1920 × 1080 / 1280 × 1024 / 1024 × 768
HDMI2: 1920 × 1080 / 1280 × 1024 / 1024 × 768
VGA 1: 1920 × 1080 / 1280 × 1024 / 1024 × 768
VGA and HDMI1 output the same video source

Multi-screen Display Main output: 1/4/6/8/9/13/16/25/32/36 (live view)
AUX output: 1/4/6/8/9 (live view)
Max. 32+9CH local live view

AUDIO

Network input 40 CH IPC audio input

2-way Audio RCA × 1

Local Input RCA × 1

Compression G.711 (U/A)

RECORD

Resolution 16MP/12MP/9MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/
960P/720P/960H/D1/CIF

Frame Rate NTSC: 30fps; PAL: 25fps



PLAYBACK

Simultaneous Playback	Max 16CH
Search	Time slice/time/event/tag/smart search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc

DECODING CAPABILITY

Live View/Playback	Non-AI Mode: 1×16MP@30fps/4×8MP@30fps/9×3MP@30fps/ 16×2MP@30fps AI Mode:1×16MP@30fps/4×6MP@30fps/9×3MP@30fps/ 16×720P@30fps
--------------------	--

ALARM

Mode	Manual, sensor, motion, exception, smart events, etc.
Input	8 CH local alarm input
Output	4 CH
Triggering	Record, snap, preset, e-mail, etc.

FACE

Face Detection Performance (AI by IPC)	40CH
Face Detection Performance (AI by Device)	2 CH (2MP)
Face Match Performance	6 CH
Comparison Capability	18 pictures / second
Face Picture Database	32 libraries 10000 face pictures
Face Picture Search	Search by picture is supported
Database Management	Add, modify, delete and search face pictures



An ISO 9001:2008 Certified Company

Face Picture Adding	Add face pictures through APP, WEB and external import
Face Picture Comparison	Support allow list, block list and stranger match alarm
Track	Track display on a map
Statistical Graph of Information	Bar graph
Statistical Mode of Information	Statistics by day, week, month, quarter as well as Customized time period

PERIMETER PROTECTION

Human/Vehicle Classification (AI by IPC)	40 CH
Human/Vehicle Classification (AI by Device)	2CH (2MP)

VIDEO METADATA

Human/Vehicle Attribute Analysis (AI by IPC)	Yes
---	-----

OTHER FUNCTIONS

Fisheye	Supports fisheye dewarping via NVR/Web Client/mobile APP
Plate Recognition (AI by IPC)	Yes

NETWORK

Interface	2 x RJ45 1000Mbps
Protocol	TCP / IP, HTTP, HTTPS, 802.1X, FTP, DHCP, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IPv6, IPv4, UDP, WebSocket, PPPoE, SNMP, IGMP
Client Connection	Max. 128 users access



MOBILE DEVICE

OS iOS, Andriod

STORAGE

HDD Interface SATA × 2, max 10T for each HDD

BACKUP

Local Backup U disk, USB mobile HDD

Network Backup Yes

EXTERNAL INTERFACE

RS485 Yes (full-duplex), connect to PTZ or keyboard

USB USB 3.0 × 1; USB 2.0 × 2

Remote Controller Optional

GENERAL

Power Supply DC12V/4A

Consumption ≤ 20W (without HDD)

Dimensions (mm) 380 × 268 × 48.1 (W × D × H)

Working Environment -10 ~ 50 °C, 10% ~ 90% humidity



An ISO 9001:2008 Certified Company