

HD-XVR-4108TLI



Product Features

- ≥ 8CH TVI / AHD/CVI 1080P/ 1080P Lite/720P/WD1 video input
- ≥ 8CH DVR supports 8CH 5MP/4MP/3MP/1080P / 960P /720P IP video input by default
- ≥ 8CH DVR: 8CH analog video input can be switched to 8CH IP video input
- ≥ Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- ≥ Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- ≥ Multi-mode recording: manual / timed / motion / AI recording
- ≥ Playback : 4CH simultaneously playback
- ≥ Search: time slice, time, event, tag search
- ≥ Supports Smart Motion Detection (Human/Vehicle)
- ≥ Express and flexible backup via USB, network and so on
- ≥ Pentaplex: preview, record, playback, backup and remote access
- ≥ DHCP, DDNS, PPPoE network protocol
- ≥ Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- ≥ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device Authorization management, log review and device status review
- ≥ Support 1080P output, true high resolution display
- ≥ Support PTZ preset and auto cruise, up to 255 presets and 8 cruises Support NAT function and QRCode scanning by mobile phones Powerful mobile surveillance by smart phones with iOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications:

SYSTEM

Main Processor
Operating System

Embedded Processor
Embedded LINUX

VIDEO AND AUDIO

Incoming Bandwidth
Outgoing Bandwidth
Analog Camera Input
IP Camera Input
Audio In
Audio Out
Two-way Talk

16Mbps
60Mbps
8Channel, BNC
8CH (HD) + 2CH (IPC)
RCA ×1
RCA ×1
Take up channel one audio input

RECORDING

Video Compression
Resolution
Record Rate

H.264/H.265
1080P Lite/ 720P/ 720P Lite/ WD1
Analog Channel:
8CH DVR: 1080P Lite/720P/WD1: 25fps (PAL)/30fps (NTSC)
IP Channel: 25fps(PAL) / 30fps (NTSC)
32Kbps ~ 4Mbps

Video Bit Rate

PLAYBACK

Playback
Search
Smart Search

8 CH
Time slice / time / event / tag search
Highlight colors to display the camera record in a certain period of time, different colors refer to different record events
Play, pause, FF, FB, digital zoom, etc.

Function

Smart Motion Detection

Supports



An ISO 9001:2008 Certified Company

DISPLAY

Interface	1 HDMI ,1 VGA
Resolution	1920×1080, 1280×1024, 1024×768
Multi-screen Display	1/4/6/9

NETWORK

Interface	RJ 45 100Mbps × 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP
Max. User Access	5 users

BACKUP

Local Backup	U disk, USB mobile HDD
Network Backup	Yes

STORAGE

HDD	1 SATA Port, up to 8TB capacity
-----	---------------------------------

AUXILIARY INTERFACE

USB	2 USB 2.0
-----	-----------

ELECTRICAL

Power Supply	DC12V/1.5A
Power Consumption	≤5W (Without HDD)

ENVIRONMENTAL

Operating Conditions	-10~50°C, 10%~90% (humidity)
Dimensions	255 × 222 × 42 (W × D × H)



An ISO 9001:2008 Certified Company