

HD-XVR-5432THC



Product Features :

- 32 CH TVI / AHD/CVI 5MP/ 4MP/ 3MP / 1080P / 720P / WD1 video input
- 32 CH DVRs support 8 CH 5MP / 4MP / 3MP / 1080P / 960P / 720P IP video input
- 16CH analog video input can be switched to 16CH IP video input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-type recording: manual / timed / sensor / motion /AI recording Playback: 16 CH simultaneously playback
- Search: time slice, time, event, tag and smart search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS: preview, playback, backup, PTZ and configuration
- Multi-user online simultaneously
- Authorization management, log review and device status review
- 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

OS Embedded Linux

VIDEO

Analog Video Input BNC × 3 2
 BNC interface (1.0Vp-p; 75Ω)
 TVI/AHD/CVI: 5MP@20fps;
 4MP/3MP/1080P/720P/WD1@25fps/30fps (live)

IP Video Input 8CH (up to 24CH)
 Up to 5MP@30fps

Total Input 40CH

Output HDMI × 1: 1920 × 1080 / 1280 × 1024 / 1024 × 768
 VGA × 1: 1920 × 1080 / 1280 × 1024 / 1024 × 768
 BNC × 1: CVBS (used as the main or spot output)

Compression H.264/H.265/H.265+

Multi-screen Display 1/4/6/8/9/13/16/25/32/36

AUDIO

Input RCA × 16

Output RCA × 1 (linear, 600Ω)

Two-way audio Take up channel one audio input

Compression G.711(U/A)

RECORD

Record 5MP Lite/4MP Lite / 1080P/1080P Lite/720P/WD1/D1

Frame Rate Analog Channel: 5MP Lite@10fps (PAL / NTSC);
 4MP Lite/1080P@12fps (PAL) / 15fps (NTSC);
 1080PLite/720P/WD1/D1@25fps (PAL)/ 30fps (NTSC)
 IP Channel: 25fps (PAL) / 30fps (NTSC)

Bit Rate 32Kbps ~ 5Mbps

Playback 16CH



An ISO 9001:2008 Certified Company

Search	Time slice / time / event / tag /smart search
Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events
Function	Play, pause, FF, FB, digital zoom, etc.

ALARM

Mode	Manual, motion, exception, smart event
Input	16CH
Output	4CH

AI FUNCTION

Smart Motion Detection Performance	16CH
Perimeter Protection Performance	1CH

NETWORK

Interface	RJ 45 1000Mbps × 1
Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP, etc.
Incoming Bandwidth	40Mbps (max. 88Mbps)
Outgoing Bandwidth	160Mbps
Client Connection	Max. 15users access

MOBILEDEVICE

OS	iOS, Andriod
----	--------------

STORAGE

HDD	SATA×4, up to 10TB per HDD; E-SATA×1
-----	--------------------------------------

BACKUP

Local Backup	U disk, USB mobile HDD
Network Backup	Yes



PORT

RS 485	Yes (full-duplex), connect to PTZ or keyboard
USB	USB 2.0 × 1; USB 3.0 × 1
Remote Controller	Optional

GENERAL

Power Supply	ATX-250W
Consumption	≤ 30W (without HDD)
Dimensions(mm)	440 × 390 × 70 (W × D × H)
Working Environment	-10~50°C, 10%~90% (humidity)



An ISO 9001:2008 Certified Company