

HF-EGT24



Product Features

- 24-port gigabit unmanaged desktop/rack switch designed for video surveillance in offices, work groups, and SMEs for easy, economical and high-speed internet purposes.
- Its full duplex transmission rate can reach up to 2000 Mbps, ensuring the timely transfer of large files as well as smooth streaming videos.
- ≥ The professional integrated lightening protection circuit, the built-in power supply module, and all the 24ports could withstand 6kV lightning surge, ensuring the switch to run stably.
- Upgrade to high-speed and stable gigabit wired network.



An ISO 9001:2008 Certified Company





Specifications:

Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab

Interface 24*10/100/1000M auto-negotiation

RJ45 ports (Auto MDI/MDIX)

Transmission Media 10Base-T: Cat. 3 UTP or better 100Base-TX: Cat.5 UTP or better

1000Base-T: Cat.5e UTP or better

Forwarding Speed 10Mbps: 14880pps 100Mbps: 148800pps

1000Mbps: 1488000pps

Power Input: AC: 100-240V; 50/60Hz

Lightning Level 6kV in Common Mode Protection for all ports

6kV in Common Mode, 4kV in Differential Mode Protection for

power supply

Product Dimensions (L*W*H) 294mm *178mm *44mm

LEDs 1* Power, 24* Link/Act

Switching Capacity 48Gbps

MAC Address Table 8K

Power Consumption Maximum: 13W (220V)

Transfer Method Store and Forward

Access Control CDMA/CD

MAC Address Learning Automatic update

Temperature Operating Temperature: 0°C~40°C

Storage Temperature: -40°C~70°C

Humidity Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Compatible OS Windows 8 32/64 bit, Windows 7 32/64 bit , Windows xp 32/64

Bit, Linux, MAC OS



An ISO 9001:2008 Certified Company

