

HF-HEV50-P



Product Features

- ≥ Comply with IEEE-568B standard
- ≥ Use CAT-5e/6 cable to achieve a transmission distance of 50 meters and a maximum distance of 50 meters
- ≥ Automatically adjust feedback information, balance or zoom in, users don't have to worry about the length of the cable
- ≥ Support (EQ) gain adjustment, suitable for transmission of different distances of network cable
- ≥ Supports the highest frequency resolution 1080p
- ≥ Support 165Hz / 1.65Gbps / frame rate (total frame rate 4.95Gbps) bandwidth
- ≥ Support 8 bits per frame rate (total frame rate 24 bits) dark
- ≥ Supports uncompressed 2-frame audio, such as LPCM



An ISO 9001:2008 Certified Company

Specifications:

Input video signal	0.5-1.0 v P-P, 0.5-1.0v P-P
HDMI resolution	1080p/ 1080i/ 720p/ 576p/ 576i/ 480p/ 480i
Transmission distance	Cat-5e 40 meters, 1080p
Video amplification bandwidth	1.65 Gbps/ 165Hz
Vertical frequency range	50/ 60Hz
Operating temperature	0°C to +70°C
Use humidity	10% to 85% RH (no condensation)
Infrared support	38KHz
Power	DC 5V

Package list:

- 1* 50m HDMI Extender
- 2* DC5V Power Adapter
- 1* User Manual



An ISO 9001:2008 Certified Company