

## HF-HKELIP200



### Product Features

- Support point-to-point mode, one point-to-multi point mode and cascade connection mode
- 802.3 Ethernet standard
- Support IR remote control
- Support USB mouse and keyboard extension
- The design of pure hardware, plug and play, no need for additional software



An ISO 9001:2008 Certified Company

## Specifications :

Resolutions	480p,720p,1080p
Audio	Sample rate: 32kHz,44.1kHz and 48kHz code
IR remote control	38 KHz (NEC)
Power adapter	DC: 5V/1A
The Max Power consumption	HDMI sender: 2.5W HDMI receiver 2W
Size(L-W-H)	163*87*24mm
Weight	474g x 2
Operating Temperature/Humidity	0°C-45°C/10%-80%RH (no condensation)
Storage Temperature/Humidity	-10°C-70°C/5%-90%RH (no condensation)

### HDMI TRANSMITTER

DC/5V	5V power supply for the Transmitter
HDMI – IN	HDMI input, connect HDMI signal source
HDMI-OUT	HDMI output, connect HDMI display device
IR-TX	Connect IR transmitter
USB	USB output, connect computer
Ethernet	Network interface by cat5e/6

### HDMI RECEIVER

DC/5V	5V power supply for the receiver
HDMI-OUT	HDMI output, connect HDMI signal device
IR-RX	Connect IR receiver
USB 1-2	USB input, mouse/Keyboard input
Ethernet	Network interface by cat5e/6



An ISO 9001:2008 Certified Company