

## HF-LED22AS



### Specifications:

|                    |                                     |
|--------------------|-------------------------------------|
| Panel size         | 21.5Inch                            |
| Resolution         | 1920 x 1080 Pixels                  |
| Ratio              | 16:9                                |
| Model size         | 506.4(H)*303.8(V)mm without bracket |
| Density            | 0.08265(H)x0.24795(V)mm             |
| Pixel pitch        | 0.24795H)x0.24795(V)mm              |
| viewing area       | 484.5(H)X284.4(V)mm                 |
| display area       | 476.064(H)X267.786(V)mm             |
| Brightness         | 250 cd/m <sup>2</sup>               |
| Contrast           | 1000:1                              |
| Viewing Angle(H/V) | 160/170                             |
| Response time      | 5ms                                 |



An ISO 9001:2008 Certified Company

|                    |                                            |
|--------------------|--------------------------------------------|
| Resolution         | Full HD                                    |
| Refresh Rate       | 60 Hz                                      |
| Connector Type     | VGA&HDMI                                   |
| Color display      | 16.7M                                      |
| Hardware Interface | VGA&HDMI                                   |
| Power              | 12V3A                                      |
| Consumed power     | Working:18W (Typical values) Standby:<0.5W |
| Plug and play      | Support                                    |
| User control       | Automatically adjust/Power switch          |
| OSD language       | Optional                                   |
| Speaker            | Dual 2Watts                                |
| Installation       | Bracket                                    |
| Mounting Type      | Wall Mount                                 |
| Case color         | Black                                      |
| Structure function | Bracket tilt:-4°-14°                       |
| Haze               | 25%                                        |
| Hard coating       | 3H                                         |



An ISO 9001:2008 Certified Company