

HF-PSF108



Product Features:

- (CCTV Power Supply) Comes with Individual output and resettable fuse. It ensures safe installation and delivers 1A current (Max) via each port.
- **Protections:**
It Includes Various Protections such as Overload, overvoltage, Over Current, Short Circuit, and Over Temperature Protection.
- **Voltage Adjustment Switch:**
It is useful to compensate voltage loss at camera end (12-15V DC).
- **Aesthetic:**
Unique and attractive with Ventilation for heat dissipation.
- **Strong and Durable:**
Made from High grade ABS plastic.
- **Led Indicator:**
Led indicator for each channel shows the functional status.



An ISO 9001:2008 Certified Company

Specifications:

VAC Voltage	150-265VAC
Output voltage	12~15VDC
Rated Power	75W
Ripple & Noise (max.)	144mV (max)
Voltage Adj. Range	12-15V
Device	Primary-Side Regulation
Device(frequency)	132KHz
VDS Voltage	576V (max)
Line Regulations	±1%
Load Regulations	±5%
SCP	Output short-circuit protection
OPP, OCP	Output overload/over-current protection
OVP	Output overvoltage protection, auto-restart or latching
line UV	Line brown-in/out protection
OV	Line overvoltage shutdown extends line surge withstand
OTP	Accurate thermal shutdown, hysteretic or latching
Efficiency (Typ.)	83%
Frequency Range	47-63HZ
Storage Temperature	0-50°C



An ISO 9001:2008 Certified Company