

HF-RP1002-W



Product Features

- ≥ Dual high-gain external antennas for wider coverage
- ≥ Eliminates Wi-Fi dead zones effectively
- ≥ Ethernet port supporting up to 100Mbps in AP mode
- ≥ Wi-Fi range upto 30mtrs
- ≥ Automatic configuration page for quick setup
- ≥ Ideal for medium & large households
- ≥ Network port supports dual-mode connection
- ≥ AP mode running full 100Mbps broad band
- ≥ Intelligent LED lights can help determine the best bridge location for the extender and improve the quality of signal extension
- ≥ Support IPv6 Passthrough, can access the Internet faster through IPv6 addresses



An ISO 9001:2008 Certified Company

Specifications :

HARDWARE

Interface	1x10/100Mbps RJ45 port
Antenna	2x3 dBi single-band antennas
Button	1 Reset & WPS bridge button
Power Supply	100-240V 50/60Hz, 0.3A
LED Indicator	LEDx1
Dimension	72x32x161mm (LxWxH)

WIRELESS

Wireless Standard	IEEE 802.11n/b/g@2.4 GHz
Data Rate	2.4 GHz: 300 Mbps
Frequency	11n : default 20/40MHz
Wi-fi range	30 mtrs
Wireless Modes	Repeater Mode, Access Point Mode
Wireless Security	Default encryption mode: Mix WPA-PSK/WPA2-PSK WPA algorithm: TKIP Supports black list Supports hidden SSID
Management	PC browser WEB page management, mobile browser page management

OTHERS

System Tool	LED control, System upgrade, factory reset, login password, restart
Temperature	Operating Temperature : 0°C~40°C Storage Temperature : -40C ~70°C
Humidity	Operating Humidity : 10 %~90% RH non-condensing Storage Humidity : 5 %~ 90%RH non-condensing

