

## HF-S04E2-65WH



### Product Features:

- ≥ 4\*10/100Mbps PoE RJ45 ports (port1~port4)
- ≥ 2\*10/100Mbps RJ45 ports (port5~port6)
- ≥ Maximum power of power supply: 65W
- ≥ Provide two 10/100M RJ45 uplink simultaneously
- ≥ All ports support 6KV lightning protection



An ISO 9001:2008 Certified Company

## Specifications :

Networking Ports	4*10/100Mbps PoE RJ45 ports (port1~port4) 2*10/100Mbps RJ45 ports (port5~port6)
Network Standard	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
Performance	Bandwidth: 1.2Gbps Packets Forwarding Rate: 0.89Mpps MAC table size: 1K Forwarding type: Storage and Forwarding
LED	Power Indicator LINK/ACT Indicator PoE Indicator
PoE	1/2(+), 3/6(-)
POWER	Port 4 max power: 60W PoE budget: 65W
Dimension	WxDxH: 190mmx131mmx40mm
Environment	Working Temperature: 0 ° ~ 40 °C Storage Temperature: -40°C~70°C Working Humidity: 10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90% RH non- condensing

