

HF-SG04G2F1 -75WG



Product Features :

- ≥ Supply 4*10/100/1000Mbps RJ45 self-adaption, high-speed forwarding and non-packet loss RJ45 port
- ≥ Supply 1*10/100/1000Mbps RJ45 uplink port
- ≥ Supply 1* SFP uplink port
- ≥ All ports supported by MDI/MDIX auto flip and self-negotiation. Support IEEE802.3X Full-duplex and backpressure for half-duplex mode
- ≥ 4*10/100/1000Mbps RJ45 port support POE+, meets the requirements for security monitoring, teleconference system, and wireless coverage
- ≥ Detect the PD devices automatically and supply the power without damaging non-POE devices



An ISO 9001:2008 Certified Company

Specifications :

Network Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Port	4*10/100/1000Mbps RJ45 port 1*10/100/1000Mbps RJ45 uplink port 1*1000Mbps SFP uplink port
POE power	4*10/100/1000Mbps RJ45 port support POE+ The whole power is 78W Each port max. power supply reached 30W
POE Connection	Both1/2+, 3/6- and 4/5+, 7/8- End-span
Performance	Store and forward MAC address table 2k Switching capacity 12Gbps
Forwarding Rate	10BASE-T:14880PPS/port 100BASE-tx: 148800pps/port 1000BASE-tx: 1488000pps/port
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and backpressure for half-duplex mode
Environment	Operating Temperature: -10°C - -55°C
Power	Built in power base board Input: 220V, 50HZ, Output: DC52V±5% 1.5A ≤78W
Weight &Size	1KG 200mm×118mm×44mm (L×W×H)

