

HF-SG08G2F2-150WG



Product Features:

- ≥ 8x100/1000mbps POE port; 2x100/1000mbps uplink port; 2x100/1000mbps SFP
- ≥ Watchdog, VLAN, QOS
- ≥ Support IEEE802.3AF/AT
- ≥ Whole Power: 120W (52V 2.3A)
- ≥ All port supported by MDI/MDIX auto flip and self negotiation
- ≥ Supply 100/1000Mbps adaptive high speed forwarding data packet non-lost port.
- ≥ Support IEEE802.3x flow control for Full-duplex mode and back pressure for Half-Duplex mode.
- ≥ Each port max. power supply reached 30W.

Application:

- ≥ Wireless Access Point
- ≥ IP Camera, IP Phone
- ≥ Computer Networks



An ISO 9001:2008 Certified Company



Specifications :

Product	8+2+2 port Full gigabit PoE Switch
POE Port	1 to 8 support IEEE802.3AF/AT Standard
Output Power	15.4W/30W IEEE802.3af/at
Power Pin	1/2+、3/6-
POE Protocol	IEEE 802.3af/IEEE 802.3at
POE Type	End-span
Power/Data Distance	≤100m
Network Standard	IEEE 802.3、IEEE802.3u、802.3x、802.3af/at
Network Medium	10/100BASE-TX:5 class and above non shielded twisted Pair
Switch Capability	12Gbps
Forwarding Mode	8.92Mpps
Forwarding Rate	8.92Mpps
MAC Address	MAC address table 2K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps; POE Status Indicator; Power indicator; Extender
Working Environment	Working temperature : -10°-- 55°C Storage temperature: -40°-- 85°
Weight	1.5Kg
Size	350mmx240mmx90mm



An ISO 9001:2008 Certified Company

