

## HF-SGFH16-300W



### Product Features

- Supports IEEE 802.3af / at standard, automatically detects and identifies devices that comply with the IEEE 802.3af / at standard and supply power to it
- Support Auto MDI/MDIX ;
- Adopt store-and-forward exchange method
- Intelligent power supply, the lowest power consumption, ensure PD power needs
- Provided With power circuit protection, protect the safety of PD
- No configuration characteristics of the power supply is automatically supplied to the adaptive Equipment;
- Fanless design, energy saving and environmental protection; no noise, reduce the impact on the environment
- Small, exquisite design
- Support port without link power saving function
- All ports have wire-speed forwarding capability
- Plug and play ,easy to use



An ISO 9001:2008 Certified Company

## Specifications:

Network Protocol and Standard	IEEE 802.3i,IEEE 802.3u,IEEE 802.3x IEEE 802.3ab,IEEE 802.3af,IEEE 802.3at
Port	16 10/100Mbps RJ45 port 2 10/1000Mbps RJ45 port 2 Gigabite SFP port
PoE	16 10/100Mbps RJ45 port support PoE Max power 150W Single port max 30W
Indicator	18 Link/Act LEDs 16 POE LEDs 1 Power LEDs
Performance	Forwarding mode: Store-and-Forward Switch Volume(Full-duplex):7.2Gbps Packet forwarding rate:5.36Mbps 8K MAC address table
Input power	100-240V/50-60Hz
Dimension(L×W×H)	(285×180×44)mm



An ISO 9001:2008 Certified Company