

## 2 MP DOME NETWORK CAMERA

### HIPC-D3022E-I2



- **2 MP Full HD** – 1920×1080 video @30fps
- **Video Compression** – Smart H.265+ / H.265 / H.264B / H.264M / H.264H
- **Low-Light Performance** – 0.02Lux (F2.0, AGC ON), 0Lux with IR
- **Night Vision** – Up to 30m IR range
- **Built-in Microphone** – Real-time audio capture
- **Power Options** – PoE IEEE 802.3af (Max. 7W)



1/2.8" CMOS  
IMAGE SENSOR



2 MEGAPIXEL



BUILT IN  
MIC



30M IR  
DISTANCE



IP66

#### SYSTEM OVERVIEW

2MP Dome IP Camera delivers clear Full HD video with smart IR and white light for reliable day and night monitoring. Built-in mic, intelligent detection, and efficient H.265 compression enhance security performance, while the IP66-rated design ensures dependable surveillance.

#### WHAT IS HIT TECHNOLOGY ?

HIT (HI-FOCUS Integrated Trust) is a next-generation security framework that strengthens surveillance systems with advanced cyber security and intelligent design. By integrating encrypted data transmission, secure device authentication, and protected remote access, HIT ensures surveillance systems remain secure, reliable, and trusted.

#### ABOUT HIFOCUS

HI-FOCUS is a trusted leader in surveillance and networking solutions with more than a **Decade of experience** in CCTV Industry. We deliver innovative, reliable, and high-performance security products designed to meet global quality standards. Every HI-FOCUS product is engineered with precision and rigorously tested to ensure superior performance and customer satisfaction.




### Motion Detection Protection

Instant motion detection with real-time alerts and sound & light alarms for enhanced home security



### See Every Detail in 2MP

Sharper. Clearer. Smarter Indoor Security.



### Advanced Weather proof Security Solutions

Rain or dust, an IP66-rated camera ensures reliable outdoor security. Weatherproof, durable, and built to perform in any condition.

30m  IR Day vision Mode

30m  IR Night Vision Mode

Human & Vehicle Triggered Mode



### Built-in Mic

Support 1-Way Audio Recording



### Educational Institutions & ATM

Ensure student and staff safety across classrooms, hallways, and campus areas. 24/7 remote monitoring ensure customer safety and prevent fraud with smart surveillance designed for ATM environments.





## 2MP DOME NETWORK CAMERA | HIPC-D3022E-I2

### Dual Stream

Dual Stream technology enables the CCTV camera to send two video streams simultaneously one high quality stream for clear recording and storage, and a secondary low bandwidth stream for smooth live viewing on mobile apps and remote access. This ensures sharp footage, faster streaming, and efficient bandwidth usage, making everyday monitoring reliable and hassle-free.

### OSD

The intuitive OSD menu enables quick, precise control of image and detection settings for optimal performance in any environment.

### IR Distance

The camera is equipped with IR LEDs that provide clear night vision, capturing objects up to 30 meters even in complete darkness. This ensures reliable surveillance around the clock, making it ideal for homes, offices, and outdoor areas. With enhanced visibility in low-light conditions, it strengthens security and helps monitor every detail effectively..

### Built-in Mic

The camera features a built-in microphone for real-time audio capture. It records clear sound directly from the monitored area. Ideal for monitoring conversations or ambient noises for security. Enhances overall surveillance by combining both video and audio monitoring.

### IP66 Ingress Protection

Crafted with an IP66-rated enclosure for superior protection against dust and moisture. Adds an extra layer of durability beyond standard indoor requirements. Ensures long-term reliability and consistent performance over time.



## CORE FEATURES

### CAMERA

Image Sensor	1/2.8" CMOS Starvis Sony Image Sensor
Minimum illumination	Color: 0.02Lux@(F1.6, AGC ON), B/W: 0Lux with IR
Shutter Speed	1s-1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
Smart IR	upto 30m
Wave length	850nm
WDR	120dB
s/N	>39dB
Focal Length	4mm
Aperture Range	F2.0
Aperture Type	Fixed
Digital Zoom	16x

### VIDEO

Video Compression	Smart H.265/H.265/H.264B/ H.264M/H.264H
Video Bit Rate	32k~16Mbps
Audio Compression	G.711A/G.711U/ADPCM_D
Audio Sampling Rate	8kHz/32kHz/48kHz
Max. Resolution	2MP, 1920×1080@30fps
Main Stream	PAL:25fps (1920×1080, 1280×720, 640×480, 704×576) NTSC:30fps (1920×1080, 1280×720, 640×480, 704×480)
Sub Stream	PAL:25fps (704×576, 704×288, 640×360, 352×288) NTSC: 30fps (704×480, 704×240, 640×360, 352×240)
BLC	Supported
HLC	Supported
AGC	Supported
3DNR	Supported

### White Balance

Auto/Semi-auto/Manual/Sunny/  
Natural light/Warm light/Sodium  
lamp/Incandescent lamp/  
Locked white balance

### ROI

8 regions

### OSD

3 regions; 16x16/32x32/48x48

### Defog

Supported

### Privacy Mask

4 regions

### INTELLIGENT ANALYSIS

### Basic Event

Tripwire, Perimeter, Motion  
Detection, Mask Alarm, IP Address  
Conflict, Network Disconnection,  
Trigger Warmlight, Trigger Capture

### Rules of Behavior Analyse In 1 Scene

2

### SECURITY

### Cyber Security

AES 256-bit Encryption,  
Configuration encryption,  
trusted execution, Digest,  
security logs, account lockout,  
syslog, video encryption,  
IP/MAC filtering, HTTPS,  
trusted upgrade, trusted boot

### INTERFACE

### Network Interface

1 RJ45 10M/ 100M self adaptive  
Ethernet port

### Built-in Mic

Supported

### NETWORK

### Protocols

RTSP, HTTP, HTTPS, TCP, UDP, UPnP,  
ICMP, DHCP, DNS, DDNS, Easy  
DDNS, NTP, TLS v1.2, QoS, IPv4, SSH,  
Unicast, FTP

### System Compatibility

ONVIF (Profile S/T), SDK, CGI

### Remote Connection

≤2



## GENERAL

Operating Temperature	-30°C~60°C(-22°F~140°F)
Operating Humidity	≤95%RH
Storage Temperature	-30°C~60°C(-22°F~140°F)
Storage Humidity	≤95%RH
Power Supply	PoE: IEEE 802.3af, Max. 7W
Ingress Protection	Surge protection 4000V, ESD6000V, IP66
Certification	EMI/EMC, ISO9001, CE, FCC and RoHS, BIS, STQC approved compliance report, REACH, ESD 4KV, BIS-ER-01, BIS-IS-13252
Package Dimensions	140(L)140(W)120(H)mm
Gross Weight	0.42Kg



## Dimensions

