

4 MP BULLET NETWORK CAMERA

HIPC-T4804-DLS-R1



- **4 MP High Definition** – 2560×1440 video @25fps
- **Video Compression** – H.265 / H.264 for efficient storage and bandwidth
- **Low-Light Performance** – 0.001Lux (color), 0Lux with IR
- **Night Vision** – 80m IR range + 30m white light
- **Built in Mic**– Built-in microphone and speaker
- **Power Options** – DC12V ±25% / PoE (IEEE 802.3af)
- **Power Consumption** – Low power usage, max. 7W
- **IP67 Protection** – Waterproof and dustproof for outdoor use



1/3" CMOS
IMAGE SENSOR



4 MEGAPIXEL



BUILT IN
MIC



BUILT IN
SPEAKER



IP67

SYSTEM OVERVIEW

4MP Bullet IP Camera powered by a CMOS Image sensor delivers clear day/night imaging with long range IR and white light. Built-in audio, efficient compression, and strong cybersecurity are housed in a rugged IP67-rated design for reliable outdoor surveillance.

ABOUT HIFOCUS

HI-FOCUS is a trusted leader in surveillance and networking solutions with more than a **Decade of experience** in CCTV Industry. We deliver innovative, reliable, and high-performance security products designed to meet global quality standards. Every HI-FOCUS product is engineered with precision and rigorously tested to ensure superior performance and customer satisfaction.

WHAT IS HIT TECHNOLOGY ?

HIT (HI-FOCUS Integrated Trust) is a next-generation security framework that strengthens surveillance systems with advanced cyber security and intelligent design. By integrating encrypted data transmission, secure device authentication, and protected remote access, HIT ensures surveillance systems remain secure, reliable, and trusted.





FULL COLOR NIGHT VISION

NIGHT VISION

Enhanced Visibility, Maximum Safety

With 80m IR and 30m white light illumination, this camera delivers clear footage of vehicles and pedestrians even in low-light conditions. Ideal for parking areas and perimeters, it helps deter theft and provides reliable video evidence.



Dear, I'm back



Welcome back, dear

Smarter Security with Two-Way Audio

Real-time two-way audio for smarter security. Monitor, communicate, and protect with confidence



Industrial-Grade Protection

Designed with durable IP67-rated housing, this camera performs reliably in harsh environments like warehouses and outdoor yards, providing continuous monitoring to protect goods, equipment, and critical areas.





4MP BULLET NETWORK CAMERA | HIPC-T4804-DLS-R1

Dual Stream

Dual Stream technology enables the CCTV camera to send two video streams simultaneously one high quality stream for clear recording and storage, and a secondary low bandwidth stream for smooth live viewing on mobile apps and remote access. This ensures sharp footage, faster streaming, and efficient bandwidth usage, making everyday monitoring reliable and hassle-free.

OSD

The intuitive OSD menu enables quick, precise control of image and detection settings for optimal performance in any environment.

Dual Light Night Vision

Equipped with Smart IR illumination up to 80 meters and white light up to 30 meters, the camera maintains clear visibility in low-light environments. The dual-light design supports consistent image clarity even in complete darkness.

Built in Mic

Integrated microphone enables clear audio capture along with video monitoring. Enhances situational awareness by recording sound from the monitored area. Ideal for applications requiring both visual and audio surveillance.

IP67 Ingress Protection

Designed for outdoor use, the camera features IP67-rated ingress protection, ensuring complete resistance against dust and strong protection from rain, splashes, and harsh weather conditions. It delivers reliable performance in all seasons, making it ideal for continuous outdoor surveillance.



CORE FEATURES

CAMERA

Image Sensor	1/3" CMOS Image Sensor
Minimum illumination	Color:0.001Lux@(F1.6,AGC ON), B/W:0Lux with IR
Shutter Speed	1s~1/100000s
Day&Night	IR-cut filter with auto switch (ICR)
Smart IR	Up to 80m
Wave length	850nm
White Light Distance	30m
WDR	DWDR
Focal Length	4mm/6mm
Aperture Range	F1.6
Aperture Type	Fixed

VIDEO

Video Compression	H.265, H.264
Video Bit Rate	128~6144kbps
Audio Compression	G.711U
Max. Resolution	4MP, 2560×1440 @25fps
Main Stream	25fps(2560 x1440, 2304 x 1296, 1920×1080, 1280×720)
Sub Stream	25fps(704×576, 352×288)
AGC	Supported
3DNR	Supported
ROI	Supported
OSD	4 areas
Privacy Mask	4 areas

SECURITY

Cyber security	AES 256-bit Encryption, Configuration encryption, trusted execution, Digest, security logs,account lockout, syslog, video encryption, IP/MAC filtering, HTTPS, trusted upgrade,trusted boot
----------------	---

INTERFACE

Audio	1 Channel IN/ 1 Channel OUT
Network Interface	1×RJ-45 (10/100 Base-T)
Built-in Mic	Supported
Built-in Speaker	Supported

NETWORK

Protocols	TCP, UDP, HTTP, HTTPS, DNS, RTSP, RTMP, DDNS, SMTP, FTP, NTP, DHCP, IGMP, ICMP
User/Host	8 users
Web	IE10+, Firefox52+, Edge89+, Safari11+, Chrome57+

GENERAL

Operating Temperature	-30°C~60°C(-22°F~140°F)
Operating Humidity	≤95%RH
Storage Temperature	-30°C~60°C(-22°F~140°F)
Storage Humidity	10%~95%RH(non-condensing)
Ingress Protection	IP67
Certification	EMI/EMC, ISO9001, CE, FCC and RoHS, BIS, STQC approved compliance report, REACH, ESD 4KV, BIS-ER-01, BIS-IS-13252
Power Supply	DC12V±25%, Max. 6.5W PoE: IEEE 802.3af, Max. 7W
Package Dimensions	180(L)90(W)95(H)mm
GrossWeight	0.3Kg
NetWeight	0.25Kg



Dimensions

