

HF-SGGFS04-65W



Product Features

- ≥ 4 Port 10/100/1000Base-T Ethernet ports, 2 Port 10/100/1000Base-T Uplink ethernet port, 2 Port 10/100/1000 Mbps SFP Port
- ≥ The 4 port (RJ45 ethernet port) Support IEEE802.3 af/at PoE protocol, An PoE RJ45 port can supply maximum power output of 25.4W
- ≥ Support 10/100/1000mbps auto-negotiate
- ≥ Support Half/Full duplex adaptive, and auto MDI/MDI-X function
- ≥ All port support wire-speed forwarding
- ≥ Support desktop and wall-mounted installation
- ≥ Plug and Play, no configuration requirements
- ≥ Metal case, internal power supply, Excellent heat dissipation performance can let the product running stable for a long time



Specifications :

Network Standard	IEEE 802.3 10Base-T; IEEE802.3u 100Base-TX; IEEE802.3ab 1000Base-T; IEEE802.1W Spanning Tree; IEEE 802.3x flow Control
Connector Type	1x4 RJ45, 1x2 RJ45
Transmission rate	10/100/1000Mbps auto-negotiate
Transmission distance	10Base-T: ≤250m (CAT3,4,5 UTP) 100Base-TX: ≤100m (CAT3,4,5 UTP) 1000Base-T: ≤100m (CAT3,4,5 UTP)
Forward method	Store-and-forward (full wire-speed)
Transmission mode	Half/Full duplex adaptive
MAC address table	2K
Case space	1Mb
Jumbo frames	9216b
Packet Forwarding Rate	8.928Mpps@64byte
Bandwidth	12G (non-blocking)
Power indicator	Red, PWR
Link/Act indicator	Yellow, 1 for each ethernet port
1000M indicator	Green, 1 for uplink port 5-6
PoE indicator	Green, 1 for poe port 1-4
Input voltage	AC100~240V, 50Hz
Power consumption	Standby: ≤2W; whole: ≤65W
PoE pin	1/2+,3/6-
The port max rate	≤25.4W
Operating Temperature	-20°C~60°C
Storage Temperature:	-40°C~85°C
Operating Humidity	5%~95% non-condensing



An ISO 9001:2008 Certified Company