

HC-T2400N3M-SL



Product Features

- ≥ 1080P real-time image, high resolution, true color
- ≥ AHD / TVI / CVI lossless HD video output
- ≥ Support 960H CVBS output
- ≥ Up to 1000 TVL resolution
- ≥ CMOS progressive scan, perfectly capturing the moving object Support OSD menu
- ≥ High speed, long distance and real time transmission
- ≥ Support noise reduction function
- ≥ 30m Full Colour Night view
- ≥ Support coaxial audio transmission
- ≥ Support COC
- ≥ IP67



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/ 2.8" CMOS
Resolution	2.4 MP
Image Size	1920 x 1080
Video Output	AHD/TVI/CVI/CVBS
Image System	PAL/NTSC
Electronic Shutter	Auto
IR Distance	30m (2PCS 3600K soft Warm light)
Frame Rate	30fps (60Hz); 25fps (50Hz)
Min. illumination	0 lux with IR
Lens	3.6mm
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP67

FUNCTIONS

Function Control	OSD (COC Control)
Smart LED	Manual or Auto mode
Digital WDR	Supported
Digital DNR	2D DNR
AGC	Supported
Auto White Balance	Supported
BLC	Supported
HLC	Supported
Sharpness	Supported
Contrast	Supported



An ISO 9001:2008 Certified Company

Image Setting

Yes

Defect Correction

Auto

Angle Adjustment

Pan: 0°~360° ; Tilt: 0°~75°; Rotation: 0°~360°

OTHERS

Power Supply

DC 12V (± 15%)

Power Consumption

4W

Working Environment

-30°C ~ 50° C, 10% ~ 90% (relative humidity)

Material

Metal

Weight (net)

Approx. 0.39KG



An ISO 9001:2008 Certified Company