



Product Features

- 2 1080P real-time image, high resolution, true color
- > AHD / TVI / CVI lossless HD video output
- Support 960H CVBS output
- Support OSD menu
- High speed, long distance and real time transmission
- Support noise reduction function
- ≥ 24/7 full color imaging
- ≥ LED can be turned on or off automatically
- Support noise reduction function
- Support coaxial audio transmission
- ≥ IP67



An ISO 9001:2008 Certified Company

I-FOC



*Design and specification are subject to change without notice

Specifications:

AWB (Auto white balance)

WDR

HLC

BLC

OSD

Digital zoom

Lens Mount

Audio Compression

Image Settings

Noise Reduction

CAMERASensor1/2.8", proLens3.6mm/6rShutter SpeedAutoMin. IlluminationColor: 0 luIR30mS/N> 52dB

1/2.8", progressive scan, 2.4 megapixel, CMOS 3.6mm/6mm Auto Color: 0 lux (LED ON) 30m ≥ 52dB DWDR Auto/Natural/Street Lamp/Outdoor/Manual 16x 2D DNR Supported Supported M12 Supported G.711 Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser



An ISO 9001:2008 Certified Company



*Design and specification are subject to change without notice



INTERFACE

Video Output

AHD / TVI /CVI/CVBS

GENERAL

Power	12 V DC±15%
	Power consumption: Max 4 W
Working Environment	-30°C to 50°C
	Humidity 10% ~ 90% RH(non-condensing)
Ingress Protection	IP67
Weight	0.37kg
Dimensions	165.7 × 69 × 69



An ISO 9001:2008 Certified Company



*Design and specification are subject to change without notice