

HC-TQ5501N3M-A-LED



Product Features

- 5MP real-time image, high resolution, true color
- AHD / TVI / CVI lossless HD video output
- Support 960H CVBS output
- Support 1CH Built-In MIC
- Support OSD menu
- High speed, long distance and real time transmission
- Support noise reduction function
- 24/7 full color imaging
- LED can be turned on or off automatically
- Support noise reduction function
- Support coaxial audio transmission
- IP67



An ISO 9001:2008 Certified Company

Specifications:

CAMERA

Sensor	1/2.8", progressive scan, 5.0 megapixel, CMOS
Lens	3.6mm
Shutter Speed	Auto
Min. Illumination	Color: 0 lux (LED ON)
IR	30m
S/N	≥ 52dB
WDR	DWDR
AWB (Auto white balance)	Auto/Natural/Street Lamp/Outdoor/Manual
Digital zoom	16x
Noise Reduction	2D DNR
HLC	Supported
BLC	Supported
Lens Mount	M12
OSD	Supported
Audio Compression	G.711
Image Settings	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser



An ISO 9001:2008 Certified Company

INTERFACE

Audio	1CH Audio Built-In MIC
Video Output	AHD / TVI /CVI/CVBS

GENERAL

Power	12 V DC±15% Power consumption: Max 4 W
Working Environment	-30°C to 50°C Humidity 10% ~ 90% RH(non-condensing)
Ingress Protection	IP67
Weight	0.37kg
Dimensions	165.7 × 69 × 69



An ISO 9001:2008 Certified Company