

HC-TS2400N2P-A



Product Features

- ≥ 1080P real-time image, high resolution, true color
- ≥ AHD / TVI / CVI lossless HD video output
- ≥ Support 960H CVBS output
- ≥ Up to 1000 TVL resolution
- ≥ CMOS progressive scan, perfectly capturing the moving object Support OSD menu
- ≥ High speed, long distance and real time transmission
- ≥ Support noise reduction function
- ≥ 20m IR
- ≥ Support coaxial audio transmission
- ≥ IP67



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/ 2.8" CMOS
Resolution	2.4MP
Image Size	1920 x 1080
Video Output	AHD/TVI/CVI/CVBS
Audio	1CH built-in MIC
Image System	PAL/NTSC
Electronic Shutter	Auto
IR Distance	20m
Frame Rate	30fps (60Hz); 25fps (50Hz)
Min. illumination	0 lux
Lens	2.8mm, horizontal field of view: 107°
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP67

FUNCTIONS

Function Control	OSD (COC Control)
ICR	No
Digital WDR	120 dB
Digital DNR	2D DNR
AGC	Supported
Auto White Balance	Supported
Defog	No
BLC	Supported
Front Light Compensation	No
HLC	Supported
Sharpness	Supported
Contrast	Supported



An ISO 9001:2008 Certified Company

Image Setting

Yes

Defect Correction

Auto

Language

English

Angle Adjustment

Pan: 0°~360° ; Tilt: 0°~75°; Rotation: 0°~360°

OTHERS

Power Supply

DC 12V (± 15%)

Power Consumption

IR Off : < 1W; IR On : < 4W

Working Environment

-30°C ~ 50° C, 10% ~ 90% (relative humidity)

Dimensions (mm)

162.1× 74.8× 73.8

Weight (net)

Approx. 0.37KG



An ISO 9001:2008 Certified Company