

HD-NVR-7216Q



Product Features

- ≥ Support Smart H.265/H.265+/H.264 video formats
- ≥ 16-channel input
- ≥ Support mainstream cameras of ONVIF conformance (Profile S, Profile G, Profile T) and RTSP protocols
- ≥ Support 1-ch HDMI, 1-ch VGA. HDMI up to 4K (3840x2160) resolution
- ≥ HDMI and VGA independent outputs provided
- ≥ Up to 12 Megapixels resolution recording
- ≥ 2 SATA HDDs, up to 10TB for each HDD
- ≥ Various fisheye dewarping modes for live view and playback for both web interface and GU
- ≥ ANR technology to enhance the storage reliability when the network is disconnected
- ≥ Support cloud upgrade



An ISO 9001:2008 Certified Company

Specifications :

VIDEO/AUDIO INPUT

IP Video Input	16-ch
Two-way Audio Input	1-ch, RCA

NETWORK

Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS

VIDEO/AUDIO INPUT

HDMI/VGA Output	HDMI: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA: 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Audio Output	1-ch, RCA
Audio Compression	G.711A, G.711U
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/ D1/2CIF/CIF
Synchronous Playback	16-ch
Liveview display	1/4/6/8/9/16
Corridor Mode Screen	3/4/5/7/9/10/12/16



An ISO 9001:2008 Certified Company

SNAPSHOT

FTP/Schedule/Event Snapshot

16-ch snapshot, up to 1080P resolution

DECODING

Decoding format

Smart H.265/H.265/H.264

Liveview/Playback

12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/
D1/2CIF/CIF

Capability

1 x 12MP@30, 2 x 4K@30, 5 x 4MP@30, 10 x 1080P@30,
16 x 720P@30

HARD DISK

SATA

2 SATA interface

Capacity

Up to 10TB for each disk

(The maximum HDD capacity varies with environment
temperature)

Disk Group

Support

SMART

VCA Detection by Camera

Intrusion Detection, Line Crossing Detection, Enter Area,
Leave Area, Defocus Detection, Scene Change Detection,
Object Left Behind, Object Removed, Auto Tracking

VCA Search

Behavior Search, Vehicle Search

People counting

People Flow Counting, Crowd Density Monitoring

GENERAL ALARM

General Alarm

Motion, Tampering, Human Body Detection, Video Loss,
Alarm Input, Audio Detection

Alert Alarm

IP Conflict, Network Disconnected, Disk Offline,
Disk Abnormal, Illegal Access, Hard Disk Space Low,
Hard Disk Full, Recording/Snapshot Abnormal



An ISO 9001:2008 Certified Company

EXTERNAL INTERFACE

Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0 1 x USB3.0
RS485	1
Alarm In	8-ch
Alarm Out	2-ch

GENERAL

Power Supply	12V DC Power Consumption: ≤5 W (without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions (W×D×H)	380mm × 315mm ×53mm (15.0" × 12.4" ×2.1")
Weight (without HDD)	≤1.8Kg (3.97lb)



An ISO 9001:2008 Certified Company